

1. Intro. Generate SAT instances for Erdős discrepancy patterns: The sequences $(x_d, x_{2d}, \dots, x_{\lfloor n/d \rfloor d})$ are supposed to be strongly balanced, for $1 \leq d \leq n$, where a sequence (y_1, \dots, y_t) is “strongly balanced” if the corresponding sequence of ± 1 s defined by $z_j = 2y_j - 1$ has all partial sums satisfying $-2 \leq z_1 + \dots + z_k \leq 2$.

It’s easy to see that the latter property needs to be checked only for odd values of k with $3 \leq k \leq t$.

```
#include <stdio.h>
#include <stdlib.h>
int n;
⟨Subroutine 3⟩
main(int argc, char *argv[])
{
    register int d;
    ⟨Process the command line 2⟩;
    printf(" ~_sat-erdos-disc_ %d\n", n);
    printf("X%d\n", n < 720 ? 360 : 720); /* might as well save a factor of two */
    for (d = 1; 3 * d ≤ n; d++) generate(d, n/d);
}

2. ⟨Process the command line 2⟩ ≡
if (argc ≠ 2 ∨ sscanf(argv[1], "%d", &n) ≠ 1) {
    fprintf(stderr, "Usage: _%s_ n\n", argv[0]);
    exit(-1);
}
```

This code is used in section 1.

3. Our task is to generate clauses that characterize a strongly balanced sequence, and it turns out that there's a very interesting way to do this. The subroutine *generate*(d, n) makes clauses for the sequence with $y_j = x_{jd}$.

Sinz's cardinality clauses (see *TAOCP* Section 7.2.2.2) have the property that $y_1 + \dots + y_{j+k-1} \geq k$ implies S_j^k ; hence we want $S_j^{j+2} = 0$ for $j < n/2$. The dual clauses have the property that $\bar{y}_1 + \dots + \bar{y}_{j+k-1} \geq k$ implies \bar{S}_k^j ; we can rewrite this to say that S_k^j implies $y_1 + \dots + y_{j+k-1} \geq j$. Hence we also want $S_{k+2}^k = 1$ for $k < n/2$. It follows that we need only deal with auxiliary variables S_j^k when $|j - k| \leq 1$. The variables S_k^{k-1} , S_k^k , and S_k^{k+1} will be denoted respectively by dAk , dBk , and dCk .

The clauses

$$(\bar{S}_t^t \vee S_{t+1}^t) \wedge (\bar{S}_t^{t+1} \vee S_{t+1}^{t+1}) \wedge (S_t^t \vee \bar{S}_t^{t+1}) \wedge (S_{t+1}^t \vee \bar{S}_{t+1}^{t+1})$$

are needed when $n \geq 2t + 3$. The clauses

$$(\bar{y}_{2t-2} \vee S_t^{t-1}) \wedge (\bar{y}_{2t-1} \vee \bar{S}_t^{t-1} \vee S_t^t) \wedge (\bar{y}_{2t} \vee \bar{S}_t^t \vee S_t^{t+1}) \wedge (\bar{y}_{2t+1} \vee \bar{S}_t^{t+1})$$

and their duals

$$(y_{2t-2} \vee \bar{S}_{t-1}^t) \wedge (y_{2t-1} \vee S_{t-1}^t \vee \bar{S}_t^t) \wedge (y_{2t} \vee S_t^t \vee \bar{S}_{t+1}^t) \wedge (y_{2t+1} \vee S_{t+1}^t)$$

are needed when $n \geq 2t + 1$. (And we simplify these clauses for small t by using the facts that $S_j^0 = 1$ and $S_0^k = 0$.)

⟨Subroutine 3⟩ ≡

```
void generate(int d, int n)
{
    register int i, j, k, t;
    for (t = 1; 2 * t + 3 ≤ n; t++) ⟨Generate the first clauses 4⟩;
    for (t = 1; 2 * t + 1 ≤ n; t++) ⟨Generate the second clauses 5⟩;
}
```

This code is used in section 1.

4. ⟨Generate the first clauses 4⟩ ≡

```
{
    printf ("%dB%d□%dA%d\n", d, t, d, t + 1);
    printf ("%dC%d□%dB%d\n", d, t, d, t + 1);
    printf ("%dB%d□~%dC%d\n", d, t, d, t);
    printf ("%dA%d□~%dB%d\n", d, t + 1, d, t + 1);
}
```

This code is used in section 3.

```

5. <Generate the second clauses 5> ≡
{
  if (t > 1) {
    printf("~X%d□%dA%d\n", d * (t + t - 2), d, t);
    printf("X%d□~%dC%d\n", d * (t + t - 2), d, t - 1);
    printf("~X%d□~%dA%d□%dB%d\n", d * (t + t - 1), d, t, d, t);
    printf("X%d□%dC%d□~%dB%d\n", d * (t + t - 1), d, t - 1, d, t);
  }
  else {
    printf("~X%d□%dB%d\n", d, d, 1);
    printf("X%d□~%dB%d\n", d, d, 1);
  }
  printf("~X%d□~%dB%d□%dC%d\n", d * (t + t), d, t, d, t);
  printf("X%d□%dB%d□~%dA%d\n", d * (t + t), d, t, d, t + 1);
  printf("~X%d□~%dC%d\n", d * (t + t + 1), d, t);
  printf("X%d□%dA%d\n", d * (t + t + 1), d, t + 1);
}

```

This code is used in section 3.

6. Index.

argc: 1, 2.

argv: 1, 2.

d: 1, 3.

exit: 2.

fprintf: 2.

generate: 1, 3.

i: 3.

j: 3.

k: 3.

main: 1.

n: 1, 3.

printf: 1, 4, 5.

sscanf: 2.

stderr: 2.

t: 3.

- ⟨ Generate the first clauses 4 ⟩ Used in section 3.
- ⟨ Generate the second clauses 5 ⟩ Used in section 3.
- ⟨ Process the command line 2 ⟩ Used in section 1.
- ⟨ Subroutine 3 ⟩ Used in section 1.

SAT-ERDOS-DISC

	Section	Page
Intro	1	1
Index	6	4